

1	2	3	4	5	6	7	8																																																														
The product using material and processing must conform to the "WI-PZ-001" HSF technical standard control requirements			RoHS+HF																																																																		
A							NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING:LCP BLACK UL94V-0 HF. 1-2.CONTACTS:COPPER ALLOY. 1-3.SHELL:STAINLESS STEEL SUS304. 2.PLATING SPECIFICATION: 2-1.CONTACTS: Ni 50u" MIN. UNDER PLATED OVER ALL. Au PLATED ON THE FUNCTIONAL AREA OF CONTACT. 2-2. SHELL: Ni 30u" MIN. UNDER PLATED OVER ALL 3.MECHANICAL PERFORMANCE: 3-1.INSERTION FORCE: 3.57kgf MAX 3-2.REMOVAL FORCE: 0.8kgf MIN 3-3.DURABILITY:10000 CYCLES. 4.ELECTRICAL PERFORMANCE: 4-1.CURRENT RATING:1.5A 4-2.VOLTAGE RATING:5V MAX 4-3.Contact Resistance: 30m Ohm Max. 4-4.INSULATION RESISTANCE: 100MΩ MIN 4-5.Dielectric Withstanding Voltage: 100V AC Min 5.ENVIRONMENTAL PERFORMANCE: OPERATING TEMPERATURE: -30°C~+85°C. 6.PACKAGE SPEC: REEL WLM2F9-05 2 X X 0015 PLATING: Colour: 1-G/F A:Black 2-AU 3U" K:White 5-AU 15U" 6-AU 30U"																																																														
B																																																																					
C																																																																					
D																																																																					
E																																																																					
F																																																																					
G																																																																					
H	<table><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="2">PART.NO: WLM2F9-052XX0015</td><td rowspan="4">DWG.NO: ENDE05</td><td colspan="2" rowspan="3"> WanLian Teconology Co., Ltd</td></tr><tr><td>A0</td><td>NEW RELEASE</td><td>21.01.13</td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td>Wang_jr</td><td>21.01.13</td></tr><tr><td></td><td></td><td></td><td>0.0±0.35</td><td>X°REF±6°</td><td>DESIGNER</td><td>Ding_bo</td><td>21.01.13</td><td colspan="4">TITLE: MIRCO USB 5S B TYPE 四脚全插(牛角型)</td></tr><tr><td></td><td></td><td></td><td>UNIT: mm</td><td>0.00±0.25</td><td>X'±3°</td><td>DRAWN</td><td>Ou_jian</td><td>21.01.13</td><td>REV: A0</td><td>SHEET: 1/1</td></tr><tr><td></td><td></td><td></td><td>SIZE: A4</td><td>0.000±0.10</td><td>X'X' ±2°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>												REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: WLM2F9-052XX0015	DWG.NO: ENDE05	 WanLian Teconology Co., Ltd		A0	NEW RELEASE	21.01.13	LINEAR	ANGLES	APPROVED	Wang_jr	21.01.13				0.0±0.35	X°REF±6°	DESIGNER	Ding_bo	21.01.13	TITLE: MIRCO USB 5S B TYPE 四脚全插(牛角型)							UNIT: mm	0.00±0.25	X'±3°	DRAWN	Ou_jian	21.01.13	REV: A0	SHEET: 1/1				SIZE: A4	0.000±0.10	X'X' ±2°							
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: WLM2F9-052XX0015	DWG.NO: ENDE05	 WanLian Teconology Co., Ltd																																																										
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	21.01.13																																																													
				0.0±0.35	X°REF±6°	DESIGNER	Ding_bo	21.01.13	TITLE: MIRCO USB 5S B TYPE 四脚全插(牛角型)																																																												
				UNIT: mm	0.00±0.25	X'±3°	DRAWN	Ou_jian	21.01.13		REV: A0	SHEET: 1/1																																																									
			SIZE: A4	0.000±0.10	X'X' ±2°																																																																
1	2	3	4	5	6	7	8																																																														