

1		2		3		4		5		6		7		8				
The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements										RoHS								
图形																		
规格	2PIN	2PIN	2PIN 4改2	3PIN	3PIN	3PIN 4改3	4PIN 2+2	4PIN	5PIN	5PIN 正方形2+3	5PIN 180°	5PIN 260° 2+3	5PIN 360°	6PIN 360°	6PIN 258°	6PIN 8改6	7PIN	8PIN
X值	1.20	1.50	1.00	1.20	1.50	1.00	1.20+1.00	1.00	1.00	1.50+1.00	0.80	1.50+1.00	1.00	1.00	0.80	0.80	0.80	0.80

Engagemnr firce		≤50N	Rated voltage		2-5pin:60v 6-8pin:30v		PARTS	MARERIALS	TREATMENT	AMOUNT
Disengagement force		≥5N	Rated current		2-5pin:4A 6-8pin:2A	A	HOUSING	PA66+GF	SPECIFY COLOR	1
Mechanical lifespan		≥500	Insulation resirance		≥1000MΩ	B	CONTACT	BRASS	GOLD PLATED	3
IP rating		IP67/IP68	Conract resistangce		≤10MΩ	C	NUT	ALALLOY	BLACK/SILVER	1
Flammability		UL94 V-0	Operation Temperature		-40° C~105° C	D	O-RING	EPDM	BLACK	1

P/N		TITLE			
M12A03-08-113		M12防水 A-CODE 3P线端母头 B款9.0L铝螺母			

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:		DWG.NO:		
AO	NEW RELEASE			LINEAR	ANGLES	APPROVED			M12A03-08-113		ENDE05		
				0.0±0.35	X'REF±6°	DESIGNER			TITLE:				
				0.00±0.25	X'±3°	DRAWN			M12防水 A-CODE 3P线端母头 B款9L铝螺母				
			UNIT:mm	0.000±0.10	X'X' ±2°						REV: AO	SHEET: 1/1	

1

2

3

4

5

6

7

8