

1

2

3

4

5

6

7

8

The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements

RoHS

PIN位

3pin

4pin

图形

PE

3

1

2

PE

3

1

2

0.60

9.72

ø8.80

ø9.50

ø10.80

1.80

0.60

0.80

0.60

25.40

17.60

9.00

1.20

1.15

2.65

2.05

ø10.80

ø9.72

ø9.50

ø8.80

ø1.70

ø2.30

ø8.20

10.50

8.00

1.50

0.80

ø9.80

ø14.5 表面网纹

M12*1

ø13.80

5.10

5.10

ø8.20

ø10.70

ø1.70

ø2.30

1.80

0.60

0.80

0.60

10.50

8.00

1.50

0.80

ø9.80

ø14.5 表面网纹

M12*1

ø13.80

5.10

5.10

ø8.20

ø10.70

ø1.70

ø2.30

组合图

Engagemnr firce

≤50N

Rated volage

630v

Disengagement force

≥10N

Rated current

12A

Mechanical lifespan

≥500

Insulation resirance

≥1000MΩ

IP rating

IP67

Conract resistangce

≤10MΩ

Flammability

UL94 V-0

Operation Temperature

-40° C~105° C

PARTS

MARERIALS

TREATMENT

AMOUNT

A

HOUSING

PA66+GF

SPECIFY COLOR

1

B

CONTACT

BRONZE

GOLD PLATED

3~4

C

NUT

BRASS

NICKL PLATED

1

D

O-RING

EPDM

BLACK

1

E

REV.

REVISION RECORD

DATE

UNIT:mm

SIZE: A4

GENERAL TOLERANCES

SCALE: 1:1

NAME

DATE

PART.NO:

DWG.NO:

LINEAR

ANGLES

APPROVED

DESIGNER

DRAWN

TITLE:

0.0±0.35

X°REF±6°

0.00±0.25

X°±3°

0.000±0.10

X°X' ±2°

M12SXX-08-108

M12线端成型式 S 编码 母头 焊线式屏蔽 +10. 5L网纹螺母

AO

NEW RELEASE

21.11.17

WanLian Technology Co., Ltd

REV: A0

SHEET: 1/1

1

2

3

4

5

6

7

8