

	1	2	3	4	5	6	7	8						
	The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements													
A	芯数	3	4	5	6	8	12	17						
	图形													
B	适配线缆 (AWG)	22	22	22	24	24	26	26						
	导体直径 (mm)	1.0	1.0	1.0	0.8	0.8	0.6	0.6						
	额定电流 (A)	4	4	4	2	2	1	1						
C	额定电压 (V)	250	250	60	30	30	30	30						
	绝缘电阻 (MΩ)	≥1000	≥1000	≥1000	≥1000	≥1000	≥1000	≥1000						
	接触电阻 (mΩ)	≤10	≤10	≤10	≤10	≤10	≤10	≤10						
D	技术特性													
	1. 寿命：>500 mate/unmate cycles													
	2. 温度等级：-25℃~+80℃													
E	3. 盐雾：>48h													
	4. 防水等级：IP67													
	材料规格													
F	D	屏蔽壳	铆铜	镀镍	Pcs	1								
	C	外壳	黄铜	镀镍	Pcs	1								
	B	接触体材质	黄铜	镀金	Pcs	3~17								
G	A	绝缘体材质	PA尼龙	黑色	Pcs	1								
	No.	Specification	Material	Treat	Unit	Q'ty								
H	REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Technology Co., Ltd		
	AO	NEW RELEASE	21.11.17		LINEAR	ANGLES	APPROVED			M12XXX-03-223	ENDE05			
					0.0±0.35	X°REF±6°	DESIGNER			TITLE: M12防水3~17芯 线端公头 屏蔽长款		REV: A0	SHEET: 1/1	
					UNIT:mm	0.00±0.25	X°±3°	DRAWN						
				SIZE: A4	0.000±0.10	X°X' ±2°								
	1	2	3	4	5	6	7	8						