

1	2	3	4	5	6	7	8					
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements			RoHS									
			NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING: THERMOPLASTIC HIGH TEMP,UL94V-0 1-2.CONTACTS: BRASS 2.PLATING SPECIFICATION: 2-1.CONTACTS: TIN/GOLD FLASH PLATED OVER ALL. 3.MECHANICAL PERFORMANCE: 3-1.RETENTIVITY FORCE: 0.2KGF/pin min 3-2.DURABILITY: 100 CYCLES. 4.ELECTRICAL PERFORMANCE: 4-1.CURRENT RATING: 1A AC/DC RATED VOLTAGE : 300V AC/DC 4-2.CONTACT RESISTANCE: 20 mΩ MAX 4-3.INSULATION RESISTANCE: 1000MΩ Min 4-4.DIELECTRIC WITHSTANDING : 300V 5.ENVIRONMENTAL PERFORMANCE: 5-1.OPERATING TEMPERATURE: -40°C~+105°C. 6.PACKAGE SPEC: REEL 7.P/N: PH1276 10 M 0-2 XX 2 X X X 07 SERIES NO: HEIGHT: 10: 1.0mm MALE FEMALE: M-MALE ANGLE: 0-180° ROW NO: 2-DOUBLE ROW PIN Q' PY: XXPIN HOUSING: 1-PA6T COLOR: A-BLACK PLATING: A-ALL AU G/F TERMIPOINT: 2-SMT									
RECOMMEND P. C. B LAYOUT PCB TOLERANCE: ±0.05 (TOP VIEW)												
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Technology Co., Ltd	
AO	NEW RELEASE	22.05.09		LINEAR	ANGLES	APPROVED	Wang_jr	22.05.09	PH127610M0-2XX2XXX07	ENDE05		
				0.0±0.35	X'REF±6°	DESIGNER	Han_Gao	22.05.09	TITLE:			
				UNIT:mm	0.00±0.25	X'±3°	DRAWN	LanXuan_Hou	22.05.09	1.27 Double-Row Pin header SMT TYP(H1.0)		
			SIZE: A4	0.000±0.10	X'X' ±2°						REV: A0	SHEET: 1/1
1	2	3	4	5	6	7	8					