

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

ROHS

2.00

2.0*PIN NO.±0.50

2.0*PIN NO.-2.0±0.30

2.00±0.15

SQ 0.50±0.08

4.00

2.00

2.80

PH2005 20 M 0-1 XX 1 X X 10

SERIES NO:

HEIGHT: 20: 2.0mm

MALE FEMALE: M-MALE

ANGLE: 0-180°

ROW NO: 1-SINGLE ROW

PIN Q' PY: 02~80

HOUSING: 1-PA6T

COLOR: A-BLACK

PLATING: A-ALL AU G/F 1-G/F C-BRIGHT TIN

TERMIPOINT: 1-DIP

2.00

Ø0.80

RECOMMENDED P. C. B LAYOUT

P. C. B TOLERANCE: ±0.05

NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA6T,UL94V-0
1-2.CONTACTS: BRASS

2.PLATING SPECIFICATION:
2-1.CONTACTS:
GOLD FLASH/TIN OVER NICKEL

3.ELECTRICAL PERFORMANCE:
3-1.CURRENT RATING: 5A
3-2.CONTACT RESISTANCE: 30 mΩ MAX
3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 300V

4.ENVIRONMENTAL PERFORMANCE:
4-1.OPERATING TEMPERATURE: -40℃~+105℃.

5.P/N:

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE:	NAME	DATE	PART.NO:	DWG.NO:				
A0	NEW RELEASE	21.10.15		LINEAR	ANGLES	1:1			PH200520M0-1XX1XXX10	ENDE05				
				0.0±0.35	X'REF±6°	APPROVED	Wang_jr	21.10.15						
				0.00±0.25	X'±3°	DESIGNER	Gao_Han	21.10.15	TITLE: 2.0单排针H2.0W2.0 180度 L=8.8 系列 PC:2.8		REV: A0	SHEET: 1/2		
				0.000±0.10	X'X' ±2°	DRAWN	Gao_Han	21.10.15						
1		2	3	4		5	6	7	8					