





	1	2	3	4	5	6	7	8
A	The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements							
B								
C								
D								
E								
F								
G								
H								



RECOMMEND P. C. B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)



NOTE:
1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA6T,UL94V-0
1-2.CONTACTS: BRASS
2.PLATING SPECIFICATION:
2-1.CONTACTS:
GOLD FLASH PLATED OVER ALL.
3.ELECTRICAL PERFORMANCE:
3-1.CURRENT RATING: 3A
3-2.CONTACT RESISTANCE: 20 mΩ MAX
3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 500V
4.ENVIRONMENTAL PERFORMANCE:
4-1.OPERATING TEMPERATURE: -40°C~+105°C.
5.PACKAGE SPEC: REEL
6.P/N:

PH2541 25 M 0-1 XX 2 X X X 19
SERIES NO: _____
HEIGHT: _____
25: 2.5mm
MALE FEMALE: _____
M-MALE
ANGLE: _____
0-180°
ROW NO: _____
1-SINGLE ROW
PIN Q' PY: _____
02~40
HOUSING:
1-PA6T
COLOR:
A-BLACK
PLATING:
A-ALL AU G/F
TERMIPOINT:
2-SMT

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: PH254125M0—1XX2XXX19	DWG.NO: ENDE05	
A0	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28			
				0.0±0.35	X*REF±6°	DESIGNER	Han_Gao	22.10.28	TITLE: Pitch 2.54mm 180° SMT+CAP 单排排针		
				UNIT:mm	0.00±0.25	X*±3°	DRAWN	LanXuan_Hou		22.10.28	
			SIZE: A4	0.000±0.10	X*X' ±2°					REV: A0	SHEET: 1/2

