



Section A-A



Section B-B



Section C-C

PART NO: 11501TOP-XX-NK

Finish \_\_\_\_\_ No Mark

- 0A--Gold-flash 0B--2μ" 0C--3μ" 0D--4μ" 0E--5μ"
- 0F--10μ" 0G--15μ" 0H--30μ" 0I--50μ"
- 2E--Tin-plated 5A--Gold-flash



△C5      △C1      △C5

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
11501TOP-5A-NK-01	AWG#26 #32	0.5-0.90mm	Phosphor Bronze	Au1μ"Min-on Contact Area	15,000 pcs
11501TOP-2E-NK	AWG#26 #32	0.5-0.90mm	Phosphor Bronze	TIN-plated	15,000 pcs
11501TOP-XX-NK	AWG#26 #32	0.5-0.90mm	Phosphor Bronze	Gold-plated	15,000 pcs

△C6

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART. NO:	DWG. NO:
C3	TR1105310082	11.05.31	LINEAR	1:1			11501TOP-XX-NK	ENDE05
C4	变更公司名称	17.01.13	0.0±0.25	APPROVED				
C5	依TN1807020114执行	18.07.02	X° REF±6°	DESIGNER				
C6	依YB202307100001新增电镀规格	23.08.14	0.00±0.15	DRAWN	OYD	23.08.14		
			UNIT: MM				TITLE:	ZH1.5 端子
			SIZE: A4					REV: C6 SHEET: 1/1
			0.00±0.08					
			X° X'±2°					

