



NOTE:  
1.MATERIAL SPECIFICATION:  
1-1.TERMINAL: PHOSPHOR BRONZE  
2.PLATING SPECIFICATION:  
2-1.TERMINAL:  
TIN/GOLD FLASH PLATED OVER ALL.  
3.ELECTRICAL PERFORMANCE:  
3-1.CURRENT RATING: 3A  
RATED VOLTAGE : 250V  
3-2.CONTACT RESISTANCE: 30 mΩ MAX  
3-3.INSULATION RESISTANCE: 1000MΩ Min  
3-4.DIELECTRIC WITHSTANDING : 650V AC  
4.ENVIRONMENTAL PERFORMANCE:  
4-1.OPERATING TEMPERATURE: -25°C~+85°C.  
5.SUITABLE A2011 SERIES HOUSING.  
6.WIRE RANGE: AWG28#-22#  
7.PACKAGE SPEC : REEL/10000PCS  
8.P/N:  
A2011 T F X-X  
SERIES NO: \_\_\_\_\_ PLATING:  
A-ALL AU G/F  
C-BRIGHT TIN  
D-MATTE TIN  
CONNECTOR: \_\_\_\_\_  
T-TERMINAL  
MALE FEMALE: \_\_\_\_\_ METAL:  
F-FEMALE P-PHOSPHOR BRONZE  
M-MALE B-BRASS

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE:	NAME	DATE	PART.NO:	DWG.NO:		
AO	NEW RELEASE	22.11.09		LINEAR	ANGLES	1:1			A2011TFX-X	ENDE05		
				0.0±0.35	X°REF±6°	APPROVED	Wang_jr	22.11.09	TITLE: Pitch2.00mm Terminal AWG #22 -#28		REV: A0	SHEET: 1/1
				0.00±0.25	X'±3°	CHECK	XueZe_Ma	22.11.09				
				0.000±0.10	X°X' ±2°	DRAWN	LanXuan_Hou	22.11.09				