

1	2	3	4	5	6	7	8
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements							
RoHS+HF					NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING:PA66,UL94V-0 1-2.CONTACTS:BRASS H62 2.PLATING SPECIFICATION: 2-1.CONTACTS:TIN PLATED ON CONTACT AREA. 3.MECHANICAL PERFORMANCE: 3-1.INSERTION FORCE: 1KGF/PIN MAX 3-2.REMOVAL FORCE: 3KGF/PIN MIN 3-3.DURABILITY: 50 CYCLES. 4.ELECTRICAL PERFORMANCE: 4-1. RATED CURRENT : 10A RATED VOLTAGE : 250V 4-2.INSULATION RESISTANCE: 1000MΩ MIN CONTACT RESISTANCE : 30mΩ MAX 4-3.WITHSTANDING VOLTAGE:1500V AC 5.ENVIRONMENTAL PERFORMANCE: OPERATING TEMPERATURE: -40°C~+90°C. 6.PACKAGE SPEC:TRAY 7.P/N: A1 A2201 W 0-2 08 1 X X 0 SERIES NO: CONNECTOR: W-WAFER ANGLE: 0-180° ROW NO: 2-DOUBLE ROW PIN Q'PY: 02~40 COLOR: K-WHITE PLATING: C-BRIGHE TIN TERMIPOINT: 1-DIP		