



The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS



NOTE:

1.MATERIAL SPECIFICATION:

1-1.HOUSING: PA66,UL94V-0

2. ELECTRICAL PERFORMANCE:

2-1.CURRENT RATING: 3A AC/DC

2-2.CONTACT RESISTANCE: 10 mΩ MAX

2-3.INSULATION RESISTANCE: 1000MΩ Min

2-4.DIELECTRIC WITHSTANDING : 250V

3. ENVIRONMENTAL PERFORMANCE:

3-1. OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$.

4.PACKAGE SPEC: PE BAG

5. P/N:

SERIES NO: A2508 H 3 M-1 XX X X WATER CODE
CONNECTOR: O-N/A

CONNECTOR:
H-HOUSING

3-TYPE CODE

MALE FEMALE:

M-MAIF

F-FFMA

— — — — —




ROW NO: _____

1-SINGLE ROW

WATER CODE
0-N/A



COLOR:
A-BLACK
K-WHITE

- PIN Q' PY:
02~15




3P

4P-15P



Circuit	Dimensions(mm)		Circuit	Dimensions(mm)	
	A	B		A	B
02	2.50	7.30	09	20.00	24.80
03	5.00	9.80	10	22.50	27.30
04	7.50	12.30	11	25.00	29.80
05	10.00	14.80	12	27.50	32.30
06	12.50	17.30	13	30.00	34.80
07	15.00	19.80	14	32.50	37.30
08	17.50	22.30	15	35.00	39.80

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A2508H3M-1XXXX	DWG.NO: ENDE05	 WanLian Technology Co., Ltd
A0	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28			
				0.0±0.35	X°REF±6°						
				UNIT:mm	0.00±0.25	X°±3°	DESIGNER	Han_Gao	22.10.28	TITLE: Pitch 2.50mm XA Male Housing	
				SIZE: A4	0.000±0.10	X°X' ±2°	DRAWN	LanXuan_Hou	22.10.28		
										REV: A0	SHEET: 1/1