



The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS

NOTE:
1.MATERIAL SPECIFICATION:
1-1.TERMINAL: PHOSPHOR BRONZE
2.PLATING SPECIFICATION:
2-1.TERMINAL:
TIN/GOLD FLASH PLATED OVER ALL.
3.ELECTRICAL PERFORMANCE:
3-1.CURRENT RATING: 3A AC/DC
3-2.CONTACT RESISTANCE: 20 mΩ MAX
3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 1000V
4.ENVIRONMENTAL PERFORMANCE:
4-1.OPERATING TEMPERATURE: -25°C~+85°C.
5.PACKAGE SPEC : REEL
6.P/N:

SERIES NO: A2508 T 3 F X-X
CONNECTOR: T-TERMINAL
TYPE CODE
MALE FEMALE: F-FEMALE
PLATING: C-BRIGHT TIN
METAL: P-PHOSPHOR BRONZE

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A2508T3FX-X	DWG.NO: ENDE05		
A0	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28				
				0.0±0.35	X°REF±6°	DESIGNER	Han_Gao	22.10.28	TITLE: Pitch 2.50mm XA Female 端子AWG#22~#28			
				UNIT:mm	0.00±0.25					X°±3°		
				SIZE: A4	0.000±0.10	X°X' ±2°	DRAWN	LanXuan_Hou	22.10.28			
										WanLian Technology Co., Ltd	REV: A0	SHEET: 1/1

WanLian Technology Co., Ltd

REV: A0 SHEET: 1/1