

NOTE:

- A2514 T X F X-X

SERIES NO:

CONNECTOR:
T-TERMINAL

Wire range: -
1-#20~#22
2-#24~#26

MALE FEMALE:-
F—FEMALE
M—MALE

— PLATING:

$$1 - G/F$$

A-ALL AU G/F
C-BRIGHE TIN
D-MATTE TIN

METAL:

—P—PHOSPHOR BRONZE
B—BRASS
H—HIGH CONDUCTIVITY
COPPER

Ordering Information

Part NO	Wire range	DIM A	DIM B	DIM C	DIM D
A2514T1FX-X	#20~#22	1.50	2.15	2.00	2.15
A2514T2FX-X	#24~#26	1.40	2.15	2.00	1.45

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A2514TXFX-X	DWG.NO: ENDE05	 WanLian Technology Co., Ltd.
AO	NEW RELEASE	21.10.12		LINEAR	ANGLES	APPROVED	Wang_jr	21.10.12			
				0.0±0.35	X°REF±6°	DESIGNER	Han_Gao	21.10.12	TITLE: Pitch 2.50mm 180°MX FEMALE 端子 AWG 20#~26# 高导电		
				UNIT:mm	0.00±0.25	X°±3°	DRAWN	Zijun_Huang		21.10.12	
				SIZE: A4	0.000±0.10	X°X' ±2°					



WanLian Technology Co., Ltd

REV: A0

SHEET: 1/1