

1	2	3	4	5	6	7	8																																																																									
The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements				NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING: PA66,UL94V-2 2.MECHANICAL PERFORMANCE: 2-1.RETENTIVITY FORCE: 1.5KGF/pin min 2-2.DURABILITY: 30 CYCLES. 3.ELECTRICAL PERFORMANCE: 3-1.CURRENT RATING: 3A AC/DC RATED VOLTAGE : 250V AC/DC 3-2.CONTACT RESISTANCE: 20 mΩ MAX 3-3.INSULATION RESISTANCE: 1000MΩ Min 3-4.DIELECTRIC WITHSTANDING : 1000V 4.ENVIRONMENTAL PERFORMANCE: 4-1.OPERATING TEMPERATURE: -25°C~+85°C. 5.PACKAGE SPEC: PE BAG 6.P/N:				A																																																																								
RoHS								B																																																																								
								C																																																																								
								D																																																																								
				SERIES NO: A2549 H F-2 XX X X CONNECTOR: H-HOUSING MALE FEMALE: M-MALE F-FEMALE ROW NO: 2-DOUBLE ROW WATER CODE: 0-N/A COLOR: A-BLACK K-WHITE S-NATURE PIN Q'PY: 04~40				E																																																																								
				Ordering Information & <table><thead><tr><th colspan="2">Dimensions (mm)</th><th colspan="2">Poles</th><th colspan="2">Dimensions (mm)</th></tr><tr><th>A</th><th>B</th><th></th><th></th><th>A</th><th>B</th></tr></thead><tbody><tr><td>2.54</td><td>7.42</td><td>2*12P</td><td>27.94</td><td>32.82</td><td></td></tr><tr><td>5.08</td><td>9.96</td><td>2*13P</td><td>30.48</td><td>35.36</td><td></td></tr><tr><td>7.62</td><td>12.50</td><td>2*14P</td><td>32.02</td><td>37.90</td><td></td></tr><tr><td>10.16</td><td>15.04</td><td>2*15P</td><td>35.56</td><td>40.44</td><td></td></tr><tr><td>12.70</td><td>17.58</td><td>2*16P</td><td>38.10</td><td>42.98</td><td></td></tr><tr><td>15.24</td><td>20.12</td><td>2*17P</td><td>40.64</td><td>45.52</td><td></td></tr><tr><td>17.78</td><td>22.66</td><td>2*18P</td><td>43.18</td><td>48.06</td><td></td></tr><tr><td>20.32</td><td>25.20</td><td>2*19P</td><td>45.72</td><td>50.06</td><td></td></tr><tr><td>22.86</td><td>27.74</td><td>2*20P</td><td>48.26</td><td>53.14</td><td></td></tr><tr><td>25.40</td><td>30.28</td><td></td><td></td><td></td><td></td></tr></tbody></table>				Dimensions (mm)		Poles		Dimensions (mm)		A	B			A	B	2.54	7.42	2*12P	27.94	32.82		5.08	9.96	2*13P	30.48	35.36		7.62	12.50	2*14P	32.02	37.90		10.16	15.04	2*15P	35.56	40.44		12.70	17.58	2*16P	38.10	42.98		15.24	20.12	2*17P	40.64	45.52		17.78	22.66	2*18P	43.18	48.06		20.32	25.20	2*19P	45.72	50.06		22.86	27.74	2*20P	48.26	53.14		25.40	30.28					F
Dimensions (mm)		Poles		Dimensions (mm)																																																																												
A	B			A	B																																																																											
2.54	7.42	2*12P	27.94	32.82																																																																												
5.08	9.96	2*13P	30.48	35.36																																																																												
7.62	12.50	2*14P	32.02	37.90																																																																												
10.16	15.04	2*15P	35.56	40.44																																																																												
12.70	17.58	2*16P	38.10	42.98																																																																												
15.24	20.12	2*17P	40.64	45.52																																																																												
17.78	22.66	2*18P	43.18	48.06																																																																												
20.32	25.20	2*19P	45.72	50.06																																																																												
22.86	27.74	2*20P	48.26	53.14																																																																												
25.40	30.28																																																																															
								G																																																																								
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:																																																																						
AO	NEW RELEASE	21.11.17		LINEAR	ANGLES	APPROVED	Wang_jr	21.11.17	A2549HF-2XXXX	ENDE05																																																																						
				0.0±0.35	X'REF±6°	DESIGNER	Han_Gao	21.11.17	TITLE:																																																																							
				UNIT:mm	0.00±0.25	X'±3°	DRAWN	Zijun_Huang	21.11.17	Pitch 2.54mm TE 线对板 双排 Female Housing																																																																						
			SIZE: A4	0.000±0.10	X'X' ±2°						REV: A0	SHEET: 1/1																																																																				
1	2	3	4	5	6	7	8																																																																									