

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

3*3P

6

7

8

9

10

11

18.00±0.40

23.7

3*5P

15

14

12

11

5

4

2

1

22.28±0.40

4.14

16.00±0.40

14.00±0.40

3*4P

12

6

4

1

18.14±0.40

4.14

16.00±0.40

14.00±0.40

14.00±0.40

16.00±0.40

4.14

14.00±0.40

4.14

4.14

4.14

3*5P

15

14

12

11

5

4

2

1

22.28±0.40

4.14

16.00±0.40

14.00±0.40

3*4P

12

6

4

1

18.14±0.40

4.14

16.00±0.40

14.00±0.40

RoHS

NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA66

2.ELECTRICAL PERFORMANCE:
2-1.CURRENT RATING: 7A
RATED VOLTAGE : 600V
2-2.CONTACT RESISTANCE: 20 mΩ MAX
2-3.INSULATION RESISTANCE: 1000MΩ Min
2-4.DIELECTRIC WITHSTANDING : 1500V AC

3.ENVIRONMENTAL PERFORMANCE:
3-1.OPERATING TEMPERATURE: -25℃~+85℃.

4.PACKAGE SPEC:PE BAG

5.P/N:

SERIES NO:

CONNECTOR:

MALE FEMALE:

ROW NO:

C4140 H F-3 XX X X

HOUSING:
0-UL94V-0

COLOR:
A-BLACK
S-NATURE

PIN Q'PY:
09~15

3-THREE ROWS

H	REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE:	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Technology Co., Ltd	
	A0	NEW RELEASE	21.11.17		LINEAR	ANGLES	1:1	Wang_jr	21.11.17	C4140HF-3XXXX	ENDE05		
					0.0±0.35	X°REF±6°	APPROVED						
				UNIT: mm	0.00±0.25	X°±3°	DESIGNER	Han_Gao	21.11.17	TITLE: Pitch 4.14mm Female 三排 Housing		REV: A0	SHEET: 1/1
				SIZE: A4	0.000±0.10	X°X° ±2°	DRAWN	Zijun_Huang	21.11.17				
	1	2	3	4	5	6	7	8					